

# POOL & SPA VACUUM HOSE

/// LOW DENSITY POLYETHYLENE

## SPECIFICATION

This pool and spa hose utilizes high grade, corrugated ultra-low density polyethylene. This design offers high melting temperatures, superior flexibility, and high puncture and tear resistance. The non-marking cover is abrasion resistant, crush-proof, and floats like a feather. It is top of the line for pool, spa, and vacuum applications. Screw-on pool cuffs are available for extensions and equipment connections.

## ATTRIBUTES

- Design offers high melting temperature, superior flexibility, crush-proof, and buoyancy
- Color: Blue

## MATERIALS

This pool and spa hose utilizes high grade, corrugated ultra-low density polyethylene.

## APPLICATIONS

- Pool
- Spa
- Vacuum applications

## RESISTANCE

Solvents, acids, alkalis and fuels.  
(See list on website for listing of chemicals)

**Max. vacuum, inches of mercury:** 29"

**Operating temperature range:** -5°F (-21°C) to 150°F (66°C)

**Material:** Low density polyethylene

**Color:** Blue

**Toxicity:** Non-toxic

## PACKAGING

Reels

\*Custom lengths available in large quantity only. Contact your local rep to confirm availability.

## PRESSURE RANGE

O.D. INCH	I.D. INCH	WALL INCH	WORKING PRESSURE (PSI @ 70°F)
1.58	1-1/4	.165	N/A
1.81	1-1/2	.155	N/A

 **WARNING: Not intended for use with potable water.**

ITEM # SUBMITTED	_____
JOB NAME	_____
LOCATION	_____
ENGINEER	_____
CONTRACTOR	_____
PO#	_____ TAG _____



## Create Item Number

### 900-17 A B C D

e.g. 900-17500B00504: Pool & Spa Vac Hose 1-1/4" ID, Blue, 50ft Reel

ID SIZE <u>A</u>	WALL <u>B</u>	LENGTH <u>C</u>	PACKAGE <u>D</u>
50 = 1-1/4"	0 = Misc	0025 = 25ft	5 = Reels
60 = 1-1/2"		0050 = 50ft	



\*Not all size, wall thickness and length combinations available. Contact your local rep to confirm availability.