FLEXIBLE PVC SPA HOSE

/// PVC WITH RIGID PVC HELIX

SPECIFICATION

PVC compounds reinforced with a rigid PVC spiral helix make spa hose strong, flexible, and easy to handle. It conforms to any shape or contour, and is specifically sized to be glued over barbs or into standard PVC fittings. This tubing is a superior choice for spas, jetted tubs, whirlpools, or other open systems. The rugged construction makes this equally useful as a light suction or vacuum discharge hose.

ATTRIBUTES

- conforms to any shape or contour, and is specifically sized to be glued over barbs or into standard PVC fitting
- color: white

MATERIALS

Manufactured from rigid PVC spiral helix makes this tubing strong, flexible and easy to handle.

APPLICATIONS

- spas
- suction hose
- jetted tubs
- vacuum discharge hose
- whirlpools

RESISTANCE

(See list on website for listing of chemicals)

Operating temperature range: -5°F (-21°C) to 150°F (66°C)

Material: PVC with rigid PVC helix

Color: White Bend radius: 3" – 5"

PACKAGING

Coils

*Custom lengths available in large quantity only. Contact your local rep to confirm availability.

See page 2.

ITEM # SUBMITTED	
JOB NAME	
LOCATION	
ENGINEER	
CONTRACTOR	
PO#	TAG





FLEXIBLE PVC SPA HOSE

/// PVC WITH RIGID PVC HELIX

PRESSURE RANGE

I.D. Inch	O.D. Inch	WORKING PRESSURE (PSI @ 70°F)
.5	.84	100
.75	1.05	100
1	1.31	100
1.25	1.66	80
1.5	1.90	65
2	2.375	65



! WARNING: Not intended for use with potable water.

Create Item Number

900-16<u>ABCWCD</u>

e.g. 900-16300W00101: Flexible PVC Spa Hose 3/4" ID, White, 10ft Coil

ID SIZE <u>A</u>	WALL <u>B</u>	LENGTH <u>C</u>	PACKAGE <u>D</u>
20 = 1/2"	0 = Misc	0010 = 10ft	1 = Coils
30 = 3/4"		0025 = 25ft	
40 = 1"		0050 = 50ft	
50 = 1-1/4"		0100 = 100ft	
60 = 1-1/2"			
70 - 2"			



*Not all size, wall thickness and length combinations available. Contact your local rep to confirm availability.