

WASHER HOSE

/// POLYESTER REINFORCED PVC

SPECIFICATION

This strong utility hose is designed with PVC compounds reinforced with polyester braiding. The added braiding offers better fitting retention and less chance of blow-off than non-braided styles. High quality construction ensures excellent performance and longer life. This hose is designed for use as a washing machine or dishwasher inlet and drain hose.

ATTRIBUTES

- Smooth, dense bore maximizes flow and reduces sediment buildup
- Has four times the working pressure of single wall PVC
- Color: Black

MATERIALS

Our braided vinyl tubing is manufactured from polyvinyl chloride braided with polyester.

APPLICATIONS

- Chemical transfers
- Hydraulic lines
- Food and beverage lines
- Pneumatic lines
- Coolant lines
- Vacuum lines

* The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight.

RESISTANCE

Acids, alkalis, variety of chemicals, gases and liquids.
(See list on website for listing of chemicals)

Operating temperature range: -40°F (-40°C) to 125°F (52°F)

Material: Polyester reinforced PVC

Color: Black

Hardness: Durometer 83+/-3 Shore A

Toxicity: Non-toxic FDA listed material

PACKAGING

Coils, reels

*Custom lengths available in large quantity only. Contact your local rep to confirm availability.

See page 2.

ITEM # SUBMITTED _____
JOB NAME _____
LOCATION _____
ENGINEER _____
CONTRACTOR _____
PO# _____ TAG _____



WASHER HOSE

/// POLYESTER REINFORCED PVC

PRESSURE RANGE

I.D. INCH	O.D. INCH	WALL INCH	WORKING PRESSURE (PSI @ 70°F)
5/8	7/8	1/8	N/A
3/4	1	1/8	N/A
7/8	1-1/8	1/8	30
5/8	1	3/16	200
7/8	1-1/4	3/16	200
1	1-3/8	3/16	200



WARNING: Not intended for use with potable water.



Create Item Number

900-04 A B N C D

e.g. **900-04258N00101:** Washer Hose 5/8" ID X 1" OD (3/16" Wall), Black, 10ft Coil

ID SIZE A	WALL B	LENGTH C	PACKAGE D
25 = 5/8"	6 = 1/8"	0002 = 2ft	1 = Coils
30 = 3/4"	8 = 3/16"	0010 = 10ft	5 = Reels
33 = 7/8"		0025 = 25ft	
40 = 1"		0050 = 50ft	
		0100 = 100ft	
		0150 = 150ft	



*Not all size, wall thickness and length combinations available. Contact your local rep to confirm availability.